

## SECTION 10 21 13 - TOILET COMPARTMENTS

### PART 1 - GENERAL

#### 1.1 WARRANTY

- A. Special Coating Warranty: Manufacturer's standard form in which manufacturer agrees to replace defective material.
  - 1. Coating defects include, but are not limited to: chipping, flaking, cracking or discoloration.
  - 2. Warranty Period: 3 years from Substantial Completion.

### PART 2 - PRODUCTS

#### 2.1 MATERIALS

- A. Steel Sheet: Hot-dipped galvanized, ASTM A 653/A 653M, with G90 coating.
- B. Stainless-Steel Castings: ASTM A 743/A 743M.
- C. Zamac: ASTM B 86, commercial zinc-alloy die castings.

#### 2.2 STEEL UNITS

- A. Manufacturer:
  - 1. American Sanitary Partition Corporation.
  - 2. General Partitions Mfg. Corp.
  - 3. Global Steel Products Corp.
  - 4. Hadrian Manufacturing Inc.
  - 5. Sanymetal; a Crane Plumbing company.
- B. Toilet-Enclosure Style: Overhead braced.
- C. Urinal-Screen Style: Wall hung, flat panel; post to ceiling.
- D. Door, Panel, and Pilaster Construction: Seamless, metal facing sheets pressure laminated to core material; with continuous, interlocking molding strip or lapped-and-formed edge closures; corners secured by welding or clips and exposed welds ground smooth. Exposed surfaces shall be free of pitting, seam marks, roller marks, stains, discolorations, telegraphing of core material, or other imperfections.
  - 1. Core Material: Manufacturer's standard sound-deadening honeycomb of resin-impregnated kraft paper in thickness required to provide finished thickness of 1 inch for doors and panels and 1-1/4 inches for pilasters.
  - 2. Grab-Bar Reinforcement: Provide concealed internal reinforcement for grab bars mounted on units.
  - 3. Tapping Reinforcement: Provide concealed reinforcement for tapping (threading) at locations where machine screws are used for attaching items to units.
- E. Urinal-Screen Construction:
  - 1. Flat-Panel Urinal Screen: Matching panel construction.
- F. Facing Sheets and Closures: Hot-dip galvanized-steel sheet with nominal base-metal (uncoated) thicknesses as follows:
  - 1. Pilasters, Braced at Both Ends: Manufacturer's standard thickness, but not less than 0.036 inch.
  - 2. Pilasters, Unbraced at One End: Manufacturer's standard thickness, but not less than 0.048 inch.
  - 3. Panels: Manufacturer's standard thickness, but not less than 0.030 inch.

4. Doors: Manufacturer's standard thickness, but not less than 0.030 inch.
  5. Flat-Panel Urinal Screens: Thickness matching the panels.
- G. Pilaster Shoes and Sleeves (Caps): Stainless-steel sheet, not less than 0.031-inch nominal thickness and 3 inches high, finished to match hardware.
- H. Urinal-Screen Post: Manufacturer's standard post design of material matching the thickness and construction of pilasters; with shoe and sleeve (cap) matching that on the pilaster.
- I. Brackets (Fittings):
1. Stirrup Type: Ear or U-brackets; chrome-plated zamac acceptable; stainless steel preferred.
- J. Steel-Sheet Finish: Immediately after cleaning and pretreating, apply manufacturer's standard baked-on finish, including thermosetting, electrostatically applied, and powder coatings. Comply with coating manufacturer's written instructions for applying and baking.

## 2.3 ACCESSORIES

- A. Hardware and Accessories: Manufacturer's standard design, heavy-duty operating hardware and accessories.
1. Material: Chrome-plated zamac.
  2. Hinges: Manufacturer's standard paired, self-closing type that can be adjusted to hold doors open at any angle up to 90 degrees.
  3. Latch and Keeper: Manufacturer's standard surface-mounted latch unit designed for emergency access and with combination rubber-faced door strike and keeper. Provide units that comply with regulatory requirements for accessibility at compartments designated as accessible.
  4. Coat Hook: Manufacturer's standard combination hook and rubber-tipped bumper, sized to prevent in-swinging door from hitting compartment-mounted accessories.
  5. Door Bumper: Manufacturer's standard rubber-tipped bumper at out-swinging doors.
  6. Door Pull: Manufacturer's standard unit at out-swinging doors that complies with regulatory requirements for accessibility. Provide units on both sides of doors at compartments designated as accessible.
- B. Overhead Bracing: Manufacturer's standard continuous, extruded-aluminum head rail with antigrip profile and in manufacturer's standard finish.
- C. Anchorages and Fasteners: Manufacturer's standard exposed fasteners of stainless steel or chrome-plated steel or brass, finished to match the items they are securing, with theft-resistant-type heads. Provide sex-type bolts for through-bolt applications. For concealed anchors, use stainless steel, hot-dip galvanized steel, or other rust-resistant, protective-coated steel.

## PART 3 - EXECUTION (Not Applicable)

### END OF SECTION 10 21 13